

# S 187

## AUDIBLE COMPACT UNITS



- 2 tones with remote control
- Different types of installation
- Powerful sound



### TECHNICAL FEATURES

Sound frequency  
+/- 3700 Hz

Signal repetition frequency  
+/- 1Hz

Effective dB determined at a distance of 1 meter from  
sound module  
pulse sound 85 dB-continuous sound 82 dB (24VDC)

Protection degree  
IP54 according to EN 60529

Operating Voltage  
24 (18-30) V DC

Current consumption  
20 mA

Operating temperature  
-20°C + 50°C

Connections  
with screw clamps, max cable size 1,5 mm

Housing  
polycarbonate

Dimension  
62 mm x 60 mm



- Audible unit for panel mounting (Ø 22mm)

ORDER CODE

AF700CB



- Audible unit with base for standard mounting

ORDER CODE

AF70FCB



- Audible unit with base and pole

ORDER CODE

AF70HCB

# S 710

## COMPACT ELECTRONIC SOUNDERS



- Higher sound output ,100dB with tone variaton (20 dB)
- 28 tones with frequency between 500 and 2900 Hz
- Remote control of a second tone
- IP65 and easy installation

### TECHNICAL FEATURES

Sound frequency  
500 to 2.900 Hz

Effective dB determined at a distance of 1 meter from  
sound module  
103 dB

Protection degree  
IP65

Operating Voltage  
12/24V DC- 100-260V AC

Operating temperature  
-20°C + 50°C

Connections  
with screw clamps, max cable size 1,5 mm

Housing  
ABS

Dimension  
101 mm x 100 mm



- Electronic sounder 100dB 100 dB, 28 tones, IP 65, 12/24 V DC, max 32 mA.



ORDER CODE

ECX101K

- Electronic sounder 100 dB, 8 tones, IP 65, 100/260 V AC, max 32 mA.



ORDER CODE

ECX101W