

S 220

PANEL INDICATOR LAMPS \varnothing 30mm



- Ultra bright LED light, steady or flashing light
- Bright light combined with elegance
- They can be wired perpendicularly and this enables to create particular compact installations
- Easy and quick mounting
- Fixed on panel up to 15 mm thickness

TECHNICAL FEATURES

Compliance

Directive 2006/95/EC Low Voltage

Directive 2004/108/EC Electromagnetic Compatibility

Directive 2011/65/EC RhOS

Directive 2006/42/EC Machinery

Conformity to standards

EN 60947.5.1 - EN 60073 - EN 60529 - EN 60068.2.6 and 27

EN 60204.1 - EN ISO 7731 - EN 981 - IEC 536

Protection degree

IP 20 (IP65 when mounted)

Lens color

orange, blue, yellow, white, red, green

Light output

ultra bright LED, last more than 25.000

COLOR	OEDER CODES			
	Steady light Colored dome 24 V DC-AC	Steady light Neutral dome 24 V DC-AC	Flashing light Colored dome 24 V DC-AC	Flashing light Neutral dome 24 V DC-AC
●	CD S124B	CD S6124B	CD S224B	CD S6224B
●	CD S134B	CD S6134B	CD S234B	CD S6234B
●	CD S144B	CD S6144B	CD S244B	CD S6244B
●	CD S154B	CD S6154B	CD S254B	CD S6254B
●	CD S164B	CD S6164B	CD S264B	CD S6264B
●	CD S194B	CD S6194B	CD S294B	CD S6294B



MECHANICAL DRAWINGS → see page 63

IF NECESSARY, COMPLETE WITH MOUNTING ACCESSORIES → see page 35