

220 Serie

Panel **indicator** beacons

Ø 30



Small size, great brightness, elegant line.

The possibility of perpendicular wiring allows particularly compact installations and quick and easy assembly.

Lighting with **high efficiency LEDs**, steady or flashing light.

Technical features



Compliance

Directive CEE 2014/35 Low voltage - Directive CEE 2014/30
Electromagnetic compatibility - Directive CEE 2006/42 Machinery

Conformity to standards

EN 60947.5.1 - EN 60204.1 - EN 60073 - EN 60529 -
EN 60068.2.6 - EN60068-2-27 - EN ISO 7731 - EN 981 - IEC 536

Material

Polycarbonate (PC)

Protections degree

IP 20 (wired IP 65)

Voltage

24 V DC/AC

Led

High efficiency LED

Color lens



Dimensions

(Ø x ledge) 30 x 30 mm

Operating temperature

- 20° C + 50° C

Resistance to vibrations

Min 2 days (10-150 Hz)

Connections

With screw terminals and wire clamp

PANEL INDICATOR BEACON

Quick and easy assembly, also possible on panels with a thickness of 15 mm. It allows compact installations. A wide range of accessories for a customized application.



Quick **mounting**



different colors...



Steady light



COLOR	Codes and data for ordering	COLOR	Codes and data for ordering
	CD S124B		CD S6124B
	CD S134B		CD S6134B
	CD S144B		CD S6144B
	CD S154B		CD S6154B
	CD S164B		CD S6164B
	CD S194B		

Flashing light



COLOR	Codes and data for ordering	COLOR	Codes and data for ordering
	CD S224B		CD S6224B
	CD S234B		CD S6234B
	CD S244B		CD S6244B
	CD S254B		CD S6254B
	CD S264B		CD S6264B
	CD S294B		