

# 370 Serie

## Multicolor beacons

Ø 70



The evolution of industrial signaling: **for each lamp 10 different messages**, some of which are contemporary. In the presence of 2 or more simultaneous alarms, the events **are alternately illuminated in the corresponding colors**. **Light source with multicolored LEDs with excellent brightness**. Programmable lighting, fixed light, flashing or fast flashing. Prismatic light modules with diffused lighting. Long life and low consumption.

### Technical features



#### Compliance

Directive CEE 2014/35 Low voltage - Directive CEE 2014/30  
Electromagnetic compatibility - Directive CEE 2006/42 Machinery

#### Conformity to standards

EN 60947.5.1 - EN 60204.1 - EN 60073 - EN 60529 -  
EN 60068.2.6 - EN60068-2-27 - EN ISO 7731 - EN 981 - IEC 536

#### Material

Polycarbonate (PC)

#### Voltage

24 V DC

#### Current

90 mA

#### Protection degree

IP 64

#### Protection against electric shock

class II, safety insulation according to IEC 536

#### Resistance to vibrations

2 day min (10 – 150 Hz). According to EN 60068-2-6 e 27

#### Operating temperature

- 20° C + 50° C

#### Number of combinable units

max 3 in addition to the Tricolor unit

max 2 in addition to the Quadricolor unit

#### Connections

with screw terminals and wire clamp section max 1.5 mm<sup>2</sup>.  
Placed inside the wiring sector.

## QUADRICOLOR INDICATOR MULTIFUNCTION

**Quadricolor** signal lamp with bright and diffused light.

In the presence of 2 or more alarms, the lamp lights up alternately in the colors corresponding to the event.



**1 beacon** with neutral lens that alternates up to **4 colors** simultaneously

### Technical features

#### Type of optics

Double lens with vertical and horizontal triangular stripes for a correct 360 ° diffusion

#### Multicolor



#### Number of combinable units:

max 2 in addition to the Quadricolor unit

#### Light





Steady, flashing, speedy flashing or alternating flashing light

#### Voltage

24 V DC/AC

#### Current

110 mA

COLORS	Support	Codes for ordering	Functions	Voltage
		370 04Q1B	Steady light Flashing light	24 V DC / AC
		370 94Q1B	Steady light Flashing light	24 V DC / AC

## TRICOLOR INDICATOR MULTIFUNCTION

**Tricolor** signal lamp with bright and diffused light.

In the presence of 2 or more alarms, the lamp lights up alternately in the colors corresponding to the event.




**1 beacon** with neutral lens that alternates up to **3 colors** simultaneously

### **Technical features**

**Type of optics**

Double lens with vertical and horizontal triangular stripes for a correct 360 ° diffusion

**Multicolor**



**Number of combinable units:**

max 3 in addition to the Tricolor unit

**Light**









Steady, flashing, speedy flashing, alternating flashing or rotating light

**Voltage**

24 V DC/AC

**Current**

100 mA

COLORS	Support	Codes for ordering	Functions	Voltage
		370 MN4T5B 532		24 V DC / AC
		370 MZ4T5B 532	Steady light Flashing light Rotating light Multifunction	24 V DC / AC
		370 MN4T5B 632		24 V DC / AC
		370 MZ4T5B 632		24 V DC / AC

Below you can add additional light modules

## TRICOLOR INDICATOR

**Tricolor** signal lamp with bright and diffused light.

In the presence of 2 or more alarms, the lamp lights up alternately in the colors corresponding to the event.




**1 beacon** with neutral lens that alternates up to **3 colors** simultaneously

### Technical features

#### Type of optics

Double lens with vertical and horizontal triangular stripes for a correct 360° diffusion

#### Multicolor



#### Number of combinable units:

max 3 in addition to the Tricolor unit

#### Light









Steady light

#### Voltage









24 V DC

#### Current

90 mA

COLORS	Support	Codes for ordering	Functions	Voltage
		370 04T1B 532	Steady light	24 V DC
		370 04T1B 632	Steady light	24 V DC
		370 94T1B 532	Steady light	24 V DC
		370 94T1B 632	Steady light	24 V DC

Above you can add additional light modules

COLORS	Support	Codes for ordering	Functions	Voltage
		370 04T5B 532	Steady light	24 V DC
		370 04T5B 632	Steady light	24 V DC
		370 94T5B 532	Steady light	24 V DC
		370 94T5B 632	Steady light	24 V DC

Below you can add additional light modules