

# 370 Serie

## Multicolor beacons

Ø 70



The evolution of industrial signaling: **for each lamp 10 different messages**, some of which are contemporary. In the presence of 2 or more simultaneous alarms, the events **are alternately illuminated in the corresponding colors**. Light source with **multicolored LEDs with excellent brightness**. Programmable lighting, fixed light, flashing or fast flashing. Prismatic light modules with diffused lighting. Long life and low consumption.

## Technical features



### Compliance

Directive CEE 2014/35 Low voltage - Directive CEE 2014/30  
Electromagnetic compatibility - Directive CEE 2006/42 Machinery

### Conformity to standards

EN 60947.5.1 - EN 60204.1 - EN 60073 - EN 60529 -  
EN 60068.2.6 - EN60068-2-27 - EN ISO 7731 - EN 981 - IEC 536

### Material

Polycarbonate (PC)

### Operating Voltage

24 V DC

### Current consumption

90 mA

### Protection degree

IP 64

### Protection against electric shocks

class II, safety insulation according to IEC 536

### Resistance to vibrations

2 day min (10 – 150 Hz). According to EN 60068-2-6 e 27

### Operating temperature

- 20° C + 50° C

### Number of combinable units

max 3 in addition to the Tricolor unit

max 2 in addition to the Quadricolor unit

### Connections

with screw terminals and wire clamp section max 1.5 mm<sup>2</sup>.

Placed inside the wiring sector.

## QUADRICOLOR INDICATOR MULTIFUNCTION

**Quadricolor** signal lamp with bright and diffused light.

In the presence of 2 or more alarms, the lamp lights up alternately in the colors corresponding to the event.



**1 beacon** with neutral lens that alternates up to **4 colors** simultaneously

### Technical features

#### Type of optics

Double lens with vertical and horizontal triangular stripes for a correct 360 ° diffusion

#### Multicolor



#### Number of combinable units:

max 2 in addition to the Quadricolor unit

#### Light





Steady, flashing, speedy flashing or alternating flashing light

#### Operating Voltage

24 V DC/AC

#### Current consumption

110 mA

COLORS	Support	Codes for ordering	Functions	Voltage
		370 04Q1B	Steady light Flashing light	24 V DC / AC
		370 94Q1B	Steady light Flashing light	24 V DC / AC

## TRICOLOR INDICATOR MULTIFUNCTION

Tricolor signal lamp with bright and diffused light.

In the presence of 2 or more alarms, the lamp lights up alternately in the colors corresponding to the event.




1 beacon with neutral lens that alternates up to 3 colors simultaneously

### Technical features

**Type of optics**

Double lens with vertical and horizontal triangular stripes for a correct 360 ° diffusion

**Multicolor**



**Number of combinable units:**

max 3 in addition to the Tricolor unit

**Light**









Steady, flashing, speedy flashing, alternating flashing or rotating light

**Operating Voltage**

24 V DC/AC

**Current consumption**

100 mA

COLORS	Support	Codes for ordering	Functions	Voltage
		370 MN4T5B 532		24 V DC / AC
		370 MZ4T5B 532	Steady light Flashing light Rotating light Multifunction	24 V DC / AC
		370 MN4T5B 632		24 V DC / AC
		370 MZ4T5B 632		24 V DC / AC

Below you can add additional light modules

## TRICOLOR INDICATOR

**Tricolor** signal lamp with bright and diffused light.

In the presence of 2 or more alarms, the lamp lights up alternately in the colors corresponding to the event.




**1 beacon** with neutral lens that alternates up to **3 colors** simultaneously

### Technical features

#### Type of optics

Double lens with vertical and horizontal triangular stripes for a correct 360 ° diffusion

#### Multicolor



#### Number of combinable units:

max 3 in addition to the Tricolor unit

#### Light









Steady light

#### Operating Voltage









24 V DC

#### Current consumption

90 mA

COLORS	Support	Codes for ordering	Functions	Voltage
		370 04T1B 532	Steady light	24 V DC
		370 04T1B 632	Steady light	24 V DC
		370 94T1B 532	Steady light	24 V DC
		370 94T1B 632	Steady light	24 V DC

Above you can add additional light modules

COLORS	Support	Codes for ordering	Functions	Voltage
		370 04T5B 532	Steady light	24 V DC
		370 04T5B 632	Steady light	24 V DC
		370 94T5B 532	Steady light	24 V DC
		370 94T5B 632	Steady light	24 V DC

Below you can add additional light modules