

370 Serie

Multicolor **with sound**

Ø 70



The evolution of industrial signaling: **for each lamp 10 different messages**, some of which are contemporary. In the presence of 2 or more simultaneous alarms, the events are alternately illuminated in the corresponding colors.

Two-channel **horn** with the possibility of remote control.

Programmable lighting, fixed light, flashing or fast flashing. Long life and low consumption.

Technical features



Compliance

Directive CEE 2014/35 Low voltage - Directive CEE 2014/30
Electromagnetic compatibility - Directive CEE 2006/42 Machinery

Conformity to standards

EN 60947.5.1 - EN 60204.1 - EN 60073 - EN 60529 -
EN 60068.2.6 - EN60068-2-27 - EN ISO 7731 - EN 981 - IEC 536

Material

Polycarbonate (PC)

Voltage

24 V DC

Current

90 mA

Protection degree

IP 64 with sound IP 54

Protection against electric shock

class II, safety insulation according to IEC 536

Resistance to vibrations

2 day min (10 – 150 Hz). According to EN 60068-2-6 e 27

Operating temperature

- 20° C + 50° C

Number of combinable units

max 3 in addition to the Tricolor unit

max 2 in addition to the Quadricolor unit

A-weighted sound power measured at one meter

90 dB

Connections

with screw terminals and wire clamp section max 1.5 mm².

Placed inside the wiring sector.

QUADRICOLOR INDICATOR MULTIFUNCTION WITH AUDIO

Quadricolor signal lamp with bright and diffused light and audible unit.

In the presence of 2 or more alarms, the lamp lights up alternately in the colors corresponding to the event.



1 beacon with neutral lens that alternates up to **4 colors** simultaneously and with independent **two-channel horns**

Technical features

Type of optics

Double lens with vertical and horizontal triangular stripes for a correct 360 ° diffusion

Multicolor



Light

Steady, flashing, speedy flashing or alternating flashing light

Voltage

24 V DC/AC

Sound



Pulse or continuous. Remote change

Current

130 mA

Sound frequency

2900 Hz

| COLORS | Support | Codes for ordering | Functions | Voltage | Effective dB |
|---|----------------------------------|--------------------|--------------------------------|--------------|--------------|
|  | <input type="radio"/> | 370 04Q7B | Steady light Flashing light | 24 V DC / AC | 90 dB |
|  | <input checked="" type="radio"/> | 370 94Q7B | Steady light Flashing light | 24 V DC / AC | 90 dB |

TRICOLOR MULTIFUNCTION INDICATOR WITH AUDIO

Tricolor Multifunction signal lamp with audible unit.

In the presence of 2 or more alarms, the lamp lights up alternately in the colors corresponding to the event.



1 beacon with neutral lens that alternates up to **3 colors** simultaneously and with independent **two-channel horns**

Technical features

Type of optics

Double lens with vertical and horizontal triangular stripes for a correct 360 ° diffusion

Multicolor



Light

Steady, flashing, speedy flashing or alternating flashing or rotating light

Sound

Pulse or continuous. Remote change

Voltage









24 V DC/AC

Current

120 mA

Sound frequency

2900 Hz

| COLORS | Support | Codes for ordering | Functions | Voltage | Effective dB |
|---|---|--------------------|---|--------------|--------------|
|  |  | 370 MN4T7B 532 | | 24 V DC / AC | 90 dB |
|  |  | 370 MZ4T7B 532 | Steady light Flashing light Rotating light Multifunction | 24 V DC / AC | 90 dB |
|  |  | 370 MN4T7B 632 | | 24 V DC / AC | 90 dB |
|  |  | 370 MZ4T7B 632 | | 24 V DC / AC | 90 dB |

You can add light modules below

TRICOLOR INDICATOR WITH AUDIO

Tricolor signal lamp with audible unit.

In the presence of 2 or more alarms, the lamp lights up alternately in the colors corresponding to the event.



1 beacon with neutral lens that alternates up to **3 colors** simultaneously
and with independent **two-channel horns**

Technical features

Type of optics

Double lens with vertical and horizontal triangular stripes for a correct 360 ° diffusion

Multicolor



Light

Steady

Sound

Pulse or continuous. Remote change

Voltage

24 V DC/AC

Current

110 mA

| COLORS | Support | Codes for ordering | Functions | Voltage | Effective dB |
|---|---|--------------------|--------------|---------|--------------|
|  |  | 370 04T7B 532 | Steady light | 24 V DC | 90 dB |
|  |  | 370 04T7B 632 | Steady light | 24 V DC | 90 dB |
|  |  | 370 94T7B 532 | Steady light | 24 V DC | 90 dB |
|  |  | 370 94T7B 632 | Steady light | 24 V DC | 90 dB |

Above it is possible to add light modules